

**SECTION I -- IDENTIFICATION OF SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING**

**TRADE NAME:** DIAMOND DR<sup>®</sup> Synthetic Organic Dust Control<sup>®</sup>  
advanced environmental performance solution

**CHEMICAL NAME:** SYNTHETIC ORGANIC DUST CONTROL AGENT FOR BALL FIELDS

**SYNONYMS:** DUST RETARDANT

**CHEMICAL FAMILY:** N/A

**MOLECULAR WEIGHT:** N/A

**FORMULA:** N/A

**CAS REGISTRY NO.:** PRODUCT A BLEND - NO NUMBER ASSIGNED

**SECTION II -- COMPOSITION/INFORMATION ON INGREDIENTS**

<u>NAME</u>	<u>%</u>	<u>CAS REG. NO.</u>
Severely hydrotreated, hydorcracked, hydroisomerized, high viscosity synthetic iso-alkane	25 – 100	178603-64-0
Proprietary ingredients	Trace Secret	Non-hazardous

**SECTION III -- HAZARDS IDENTIFICATION**

Synthetic Product      Product is essentially non-hazardous if used as directed.  
If heated, fluid mist 8 hour TLV-TWA = 5mg/m<sup>3</sup> (ACGIH)

**SECTION IV -- FIRST AID MEASURES**

**EYES:** Flush eyes with flowing water at least 15 minutes, get medical attention.  
Do not use any eye ointment. Remove contact lenses.

**INHALATION:** If problems are experienced because of heated material, move subject to fresh air.  
If victim is not breathing perform artificial respiration. Administer oxygen if available. Keep victim warm and at rest. Seek medical attention as soon as possible.

**SKIN:** Product is essentially non-hazardous. If you experience irritation, flush with large amount of waters or wash with soap and water. Seek medical attention if irritation persists.

**INGESTION:** DO NOT induce vomiting because of aspiration into the lungs. Diamond Doctor has a laxative effect and will be eliminated quickly. Seek medical attention.  
**NEVER GIVE FLUIDS OR INDUCE VOMITING IF PATIENT IS UNCONSCIOUS OR HAVING CONVULSIONS.**

**NOTE TO PHYSICIAN:** Monitor respiratory distress. If cough or difficulty breathing develops, evaluate for respiratory tract irritation, bronchitis or pneumonitis.

## SECTION V -- FIRE FIGHTING MEASURES

<b>FLAMMABILITY:</b>	Nonflammable, but will burn an prolonged exposure to flame or high temperature.
<b>FLASH POINT (TEST METHOD):</b>	>280 <sup>0</sup> F (>138 <sup>0</sup> C), open cup, ASTM D92, Cleveland
<b>AUTOIGNITION TEMPERATURE:</b>	N/D
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS:</b>	Do not cut, weld, heat of drill or pressurize empty container.
<b>MATERIALS TO AVOID:</b>	Low fire hazard. Must be moderately heated before ignition will occur. Avoid contact with strong oxidizing agents, including peroxides, chlorine and strong acids.
<b>PRODUCTS OF COMBUSTION:</b>	Carbon dioxide, carbon monoxide, smoke and irritating fumes as products of incomplete combustion.

### EXTINGUISHING MEDIA AND INSTRUCTIONS:

If a tank, railcar or tank truck is involved in a fire isolate for 0.5 miles in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from the area and let the fire burn itself out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of the tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion.

SMALL FIRE: use dry chemicals, foam, CO<sub>2</sub>.

LARGE FIRE: use water spray, fog of foam. For small outdoor fires portable extinguishers may be used and SCBA (self contained breathing apparatus) may not be required. For all indoor fires and any significant outdoor fires SCBA if required. Respiratory and eye protection are required for firefighting personnel.

## SECTION VI - ACCIDENTAL RELEASE MEASURES

### SPILL AND LEAK PROCEDURES:

ELIMINATE ALL IGNITION SURCES. Stop leaks without risk and contain spill. Absorb with inert absorbent materials such as clay or sand. Place absorbent in closed metal containers for later disposal or burn in appropriate facility. Keep spills out of sewers and open bodies of water.

## SECTION VII -- HANDLING AND STORAGE

<b>STORAGE:</b>	Keep in a cool, dry, ventilated storage area and in closed containers. Keep away from sources of ignition and oxidizing materials.
<b>HANDLING:</b>	KEEP AWAY FROM SOURCES OF IGNITION. Do not reuse empty containers. Practice good hygiene. Wash hands before eating. Launder clothes before reuse.

**SECTION VIII -- EXPOSURE CONTROL/PERSONAL PROTECTION**

<b>RESPIRATORY PROTECTION:</b>	None required if good ventilation is maintained. If mist is generated by heating use a NIOSH approved organic respirator with a mist filter.
<b>VENTILATION:</b>	Under normal handling conditions special ventilation is not necessary. If operation generates mist or fumes use ventilation of keep exposure to airborne contaminants below exposure limits.
<b>EYE PROTECTION:</b>	Chemical splash, goggles recommended.
<b>PROTECTIVE CLOTHING:</b>	Clothing to minimize skin contact, long sleeves, boots or shoes. For casual contact PVC gloves are suitable, for prolonged contact use neoprene or nitrile gloves.

**SECTION IX -- PHYSICAL AND CHEMICAL PROPERTIES**

<b>BOILING/MELTING POINT @ 760 mm Hg:</b>	N/D
<b>VAPOR PRESSURE mm Hg @ 20°C:</b>	negligible at ambient temperature
<b>SPECIFIC GRAVITY OR BULK DENSITY:</b>	0.82 – 0.94
<b>SOLUBILITY IN WATER:</b>	insoluble in water
<b>APPEARANCE:</b>	viscous, clear liquid
<b>ODOR:</b>	none
<b>POUR POINT:</b>	N/D
<b>pH:</b>	N/A not an aqueous solution or emulsion
<b>ACIDITY:</b>	none
<b>ALKALINITY:</b>	none

**SECTION X -- STABILITY AND REACTIVITY**

<b>STABILITY:</b>	Stable under normal handling conditions.
<b>CHEMICAL INCOMPATIBILITY:</b>	Can react with strong organic oxidizing materials.
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	Heating of Diamond Dr <sup>®</sup> causes thermal decomposition. In the presence of air may yield carbon monoxide and/or carbon dioxide, smoke, hydrocarbons and irritating fumes.
<b>HAZARDOUS POLYMERIZATION:</b>	Does not occur under normal industrial conditions.
<b>CONDITIONS TO AVOID:</b>	Excessive heat and flame.
<b>CORROSIVE TO METAL:</b>	No

## SECTION XI -- TOXICOLOGICAL INFORMATION

### EFFECTS OF OVEREXPOSURE

**INHALATION:** Inhalation is highly unlikely. However prolonged or repeated inhalation of heated product fumes or mists may cause irritation to the respiratory tract and lungs and may lead to fibrosis and reduced pulmonary function.  
OSHA PEL (8 hour TWA) = 5mg/m<sup>3</sup> for synthetic fluid mists

**SKIN:** It is not a skin irritant however prolonged or repeated contact may cause skin irritation, dermatitis or oil acne.

**EYES:** Prolonged or repeated contact may be irritating to eyes. Will not cause permanent damage.

**INGESTION:** Relatively non toxic to digestive tract.

### **CARCINOGENICITY:**

**Based on studies to date Diamond Doctor is not known to be carcinogenic to humans.**

ACGIH (mists) - Based on available human studies, exposure to product mist alone has not demonstrated to cause human effects at levels below 5 mg/m<sup>3</sup>.  
IARC - IARC group 3; cannot be classified as to carcinogenicity to humans.  
NTP - No studies were found.  
IRIS - No studies were found.  
OSHA - OSHA PEL (8 hour TWA) = 5 mg/m<sup>3</sup> for synthetic product mists.

## SECTION XII -- ECOLOGICAL INFORMATION

The product has the potential for degradation by hydroxyl radicals in the troposphere under the influence of sunlight, and by bacteria in soil water. Potential for food chain concentration is low.

The acute oral toxicity toward aquatic organisms is none to low: LC50 (rainbow trout) >400,000 ppm in 96 hours; LC50 (Mysidopsis bahai) >500,000 ppm in 96 hours. Passed the EPS 1/RM/24 Microtox test luminescent bacteria.

When used and applied properly Diamond Dr will not contribute BOD.

## SECTION XIII -- DISPOSAL CONSIDERATIONS

### **WASTE DISPOSAL METHOD:**

Consult your local authorities for regulations. Preferred waste management: recycle or reuse, incinerate with energy recovery, disposal in a licensed facility. Disposal facility should be compliant with state, local and federal government regulations.

**SECTION XIV -- TRANSPORTATION INFORMATION**

D.O.T. PROPER SHIPPING NAME (49CFR172.101): None  
HAZARDOUS SUBSTANCE (40CFR116): N/A  
REPORTABLE QUANTITY (RQ): N/A  
D.O.T. HAZARD CLASSIFICATION (49CFR172.101): Non-regulated  
D.O.T. PLACARDS REQUIRED: None  
POISON CONSTITUENT (49CFR173.343): N/A  
BILL OF LADING DESCRIPTION: Synthetic organic dust suppressant  
C NO.: N/A  
UN/NA CODE: N/A

**SECTION XV-- REGULATORY INFORMATION**

EPA SARA Title III hazard class: None  
OSHA HCS hazard class: Non-OSHA hazardous (29CFR1910.1200)  
EPA SARA Title III Section 313 (40CFR372)  
Toxic Chemicals present in quantities greater than the "de minimus" level are: None

This product is not a "controlled product" under the Canadian Workplace Hazardous Material Information System (WHMIS)

**SECTION XVI -- OTHER INFORMATION**

**ABBREVIATIONS AND SYMBOLS:**

N.D. - Not Determined  
< - LESS THAN

N.A. - Not Applicable  
> - MORE THAN

N.T. - Not Tested