



GLIDEX®

## APPLICATION SHEET

### WHEN TO APPLY

Apply Glidex® track switch agent to the switch plates, throw rods, switch stand and other moveable metal switch components on a routine basis to allow the switch to throw with ease. Depending on the activity of the switch, apply Glidex® trackswitch agent bi-weekly or monthly.

### SWITCH PREPARATION

Clean or scrape off any packed up grease, graphite or other material so Glidex® track switch agent can make contact with the metal. Once the switch is cleaned, it will not be necessary to clean the switch again unless another material is put on the components. ICE FREE SWITCH® can be used during the winter season without any additional cleaning.

### HOW TO APPLY

Once the switch is clean, brush, pour, or spray Glidex® track switch agent onto the appropriate components. Spraying is usually the preferred method as it is the easiest and quickest. Put a light even coating on the surfaces to be treated. A typical application will require about 1/4 of a gallon of product. Glidex® track switch agent can be applied to a wet switch without impairing product performance.

### REAPPLICATION

As mentioned above, a bi-weekly application or monthly application should be sufficient unless your lubricating plan call for more frequent applications.

### STORAGE AND HANDLING

Glidex® track switch agent is shipped in 5-gallon containers. Shake the container slightly before filling spray applicators. It is not necessary to store the product inside, however, the container should be capped when not in use. We recommend using the product within one year of purchase.

Should you have any questions, please contact Shannon Noble at Midwest Industrial Supply, Inc. at 1-800-321-0699.



P.O. Box 8431 • Canton, OH 44711  
Toll Free: 800-321-0699 • Phone: 330-456-3121 • Fax: 330-456-3247  
E-mail: [custserv@midwestind.com](mailto:custserv@midwestind.com) • Web site: [www.midwestind.com](http://www.midwestind.com)