

MIDWEST INDUSTRIAL SUPPLY, INC.
P. O. BOX 8431
CANTON, OHIO 44711 U.S.A.

Emergency Phone Numbers: 330-456-3121

ROAD PRO® NT

MATERIAL SAFETY DATA SHEET

SECTION I -- IDENTIFICATION OF SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

TRADE NAME: ROAD PRO® NT
CHEMICAL NAME: POLYMER EMULSION MODIFIED ASPHALT EMULSION SYSTEM
SYNONYMS: MULTI-COMPONENT DUST SUPPRESSION SYSTEM
CAS REGISTRY NO.: NONE - MIXTURE
FORMULA: VARIABLE MIXTURE

SECTION II -- COMPOSITION/INFORMATION ON INGREDIENTS

<u>NAME</u>	<u>%</u>	<u>CAS REG. NO.</u>
ACRYLIC & VINYL ACETATE POLYMER	<40%	NON-HAZARDOUS
ASPHALT, PETROLEUM	<30%	008052-42-4
WATER	>30%	7732-18-5

SECTION III -- HAZARDS IDENTIFICATION

ASPHALT, PETROLEUM (FUMES)	Irritant
ACRYLIC & VINYL ACETATE POLYMER	Non-hazardous
WATER	Non-hazardous

SECTION IV -- FIRST AID MEASURES

EYES: Flush eyes immediately with copious amounts of water for at least 15 minutes, occasionally lifting the upper and lower eye lids. Get medical attention immediately.

INHALATION: If overexposure occurs, remove individual to fresh air. If discomfort continues, seek medical attention.

SKIN: Clean skin with waterless type hand cleaner followed by soap and water. If irritation develops, seek medical attention.

INGESTION: If emulsion is swallowed do not induce vomiting. Treat symptomatically and get medical attention.

MIDWEST INDUSTRIAL SUPPLY, INC.
P. O. BOX 8431
CANTON, OHIO 44711 U.S.A.

Emergency Phone Numbers: 330-456-3121

ROAD PRO[®] NT

MATERIAL SAFETY DATA SHEET

NEVER GIVE FLUIDS OR INDUCE VOMITING IF PATIENT IS UNCONSCIOUS OR HAVING CONVULSIONS.

SECTION V -- FIRE FIGHTING MEASURES

FLASH POINT (TEST METHOD): N/A In Emulsion State

AUTOIGNITION TEMPERATURE: N/A

EXTINGUISHING MEDIUM: Non Flammable in Emulsion State

NOTE: IN ASPHALT STATE: Small Fires - Use dry chemical CO₂, Halon, Water Spray or Standard Foam.
Large Fires - Use Water Spray, Fog or Standard Foam

SPECIAL FIREFIGHTING PROCEDURES: Non Flammable in Emulsion State. Material can splatter above 212°F. Dried polymer film can burn but will not support combustion.

NOTE: IN ASPHALT STATE: Move Vessel from fire area if you can do it without risk. Cool containers that are exposed to flames with water from the side until well after the fire is out. Stay away from ends of tank.

SECTION VI -- ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK PROCEDURES: Create dikes or ponds as soon as possible. Use earth, sawdust, or sand to make dikes or to use as absorbent. Upon absorption, material will revert to asphalt state and can be removed with absorption material. Keep spills out of sewers and open bodies of water.

SECTION VII -- HANDLING AND STORAGE

STORAGE: Keep in a cool, dry, ventilated storage area and in closed containers. Minimize contact with air to prevent microorganism contamination and reduce the formation of skins in the surface.

MIDWEST INDUSTRIAL SUPPLY, INC.
P. O. BOX 8431
CANTON, OHIO 44711 U.S.A.

Emergency Phone Numbers: 330-456-3121

ROAD PRO[®] NT

MATERIAL SAFETY DATA SHEET

Avoid freezing conditions.

HANDLING: Handle in a well ventilated work space.

SECTION VIII -- EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION: Normally not needed, but if conditions warrant, use organic vapor respirators.

VENTILATION LOCAL EXHAUST: As needed to remove mists or vapors.

EYE PROTECTION: Chemical goggles or safety glasses with side shields.

PROTECTIVE CLOTHING: Protective gloves with impervious coating.

OTHER: Appropriate clothing to prevent repeated or prolonged contact with skin. Under normal handling conditions the risk of exposure to residual monomer is negligible.

SECTION IX -- PHYSICAL AND CHEMICAL PROPERTIES

BOILING/MELTING POINT @ 760 mm Hg: 212°F

VAPOR PRESSURE mm Hg @ 20° C: N/D

SPECIFIC GRAVITY OR BULK DENSITY: (H₂O = 1.00): 0.99 - 1.15

SOLUBILITY IN WATER: Miscible

APPEARANCE: Brown to light tan, low viscosity

ODOR: Slight petroleum odor

SECTION X -- STABILITY AND REACTIVITY

STABILITY: Stable

CHEMICAL INCOMPATIBILITY: None

MIDWEST INDUSTRIAL SUPPLY, INC.
P. O. BOX 8431
CANTON, OHIO 44711 U.S.A.

Emergency Phone Numbers: 330-456-3121

ROAD PRO[®] NT

MATERIAL SAFETY DATA SHEET

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal Decomposition may release harmful or toxic gases: carbon dioxide, carbon monoxide, oxides of sulfur, oxides of nitrogen, reactive hydrocarbons and hydrogen sulfide.

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: None

CORROSIVE TO METAL: N/A

OXIDIZER: N/A

SECTION XI -- TOXICOLOGICAL INFORMATION

Asphalt, petroleum (heated fumes) exposure limit: 0.50mg/m³ 8-hour TWA (ACGIH)

Asphalt Emulsions have not been investigated as possible carcinogens. However, Road Pro NT contains petroleum asphalt. IARC has determined that there is inadequate evidence that undiluted, air-refined asphalt is carcinogenic to experimental animals and there is only limited evidence that undiluted steam-refined and cracking-residue asphalts are carcinogenic to animals. **IRAC has concluded that there is inadequate evidence that asphalts alone are carcinogenic to humans.**

EFFECTS OF OVEREXPOSURE

INHALATION:

Excessive exposure to fumes, vapors or mists may cause some respiratory discomfort or irritation of the mucous membranes. Asphalt when heated, releases various concentrations of hydrogen sulfide (H₂S) gas. H₂S is an extremely toxic and flammable gas that at low concentrations is irritating to the respiratory tract and has a rotten egg odor. Odor can not be relied on as means of detection because at higher concentrations H₂S causes olfactory paralysis. Even short time exposure to concentrations of 500 - 1000 ppm may lead to unconsciousness, respiratory paralysis and death.

SKIN:

Prolonged or repeated contact with cool product may cause irritation.

INGESTION:

Emulsions may cause nausea and irritation of gastrointestinal tract.

SECTION XII -- ECOLOGICAL INFORMATION

ENVIRONMENTAL STUDIES HAVE NOT BEEN PERFORMED TO DETERMINE THE EFFECT OF ASPHALT EMULSIONS ON THE ENVIRONMENT.

MIDWEST INDUSTRIAL SUPPLY, INC.
P. O. BOX 8431
CANTON, OHIO 44711 U.S.A.

Emergency Phone Numbers: 330-456-3121

ROAD PRO[®] NT

MATERIAL SAFETY DATA SHEET

ENVIROMENTAL TOXICITY STUDIES PERFORMED ON POLYMERS SIMILAR TO THOSE CONTAINED IN THE ROAD PRO NT[®] SYSTEM INDICATE THAT THE POLYMERS IN THIS PRODUCT ARE ESSENTIALLY NON-TOXIC TO THE ENVIRONMENT.

SECTION XIII -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:

Emulsion can be mixed with any stabilizing material (e.g., rock, gravel or sand) in order to change its state from a liquid into a solid. This material can then be disposed of at an approved landfill.

SECTION XIV -- TRANSPORTATION INFORMATION

D.O.T. PROPER SHIPPING NAME (49CFR172.101):	None
HAZARDOUS SUBSTANCE (40CFR116):	N/A
REPORTABLE QUANTITY (RQ):	None
D.O.T. HAZARD CLASSIFICATION (49CFR172.101):	None
D.O.T. LABELS REQUIRED (49CFR172.101):	None
D.O.T. PLACARDS REQUIRED:	None
POISON CONSTITUENT (49CFR173.343):	None
BILL OF LADING DESCRIPTION:	Emulsified Asphalt, liquid plastic, NOS
CC NO.:	N/A
UN/NA CODE:	N/A

SECTION XV-- REGULATORY INFORMATION

EPA Hazard Class: None

MIDWEST INDUSTRIAL SUPPLY, INC.
P. O. BOX 8431
CANTON, OHIO 44711 U.S.A.

Emergency Phone Numbers: 330-456-3121

ROAD PRO[®] NT

MATERIAL SAFETY DATA SHEET

OSHA Hazard Class:	Irritant
CERCLA Section 102 (a) Hazard Substance:	None
RCRA Hazardous Substance:	None
TSCA:	All of the ingredients are on the TSCA (Toxic Substance Control Act) inventory or are not required to be listed on the TSCA inventory.
California Proposition 65:	WARNING: Asphalt contains a chemical know to the State of California to cause cancer and birth defects or other reproductive harm.
WHMIS Classification:	D2B - Skin or eye irritant

SECTION XVI -- OTHER INFORMATION

ABBREVIATIONS AND SYMBOLS:

N.D. - Not Determined
< - LESS THAN

N.A. - Not Applicable
> - MORE THAN

N.T. - Not Tested