



ENVIROKLEEN®

1101 3rd Street Southeast
Canton, OH 44707 USA
330.456.3121
800.321.0699
www.midwestind.com

SAFETY DATA SHEET

SECTION I -- IDENTIFICATION OF SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

TRADE NAME: ENVIROKLEEN® Synthetic Organic Dust Control®
MANUFACTURER: Midwest Industrial Supply, Inc
1101 3rd Street SE
Canton, OH 44707
EMERGENCY PHONE NUMBER: 330-456-3121
RECOMMENDED USE: Dust Suppressant; Stabilizing Agent
CHEMICAL NAME: Isoalkane and binder system
SYNONYMS: Dust retardant and stabilization agent

SECTION II -- HAZARDS IDENTIFICATION

CLASSIFICATION: Eye Irritant, 2B
SIGNAL WORD: Warning
HAZARD STATEMENT(S): Causes eye irritation

Pictograms

PRECAUTIONARY STATEMENT(S): Flush eyes for several minutes.
Wash hands and exposed areas thoroughly.
Contact physician if irritation persists.
OTHER HAZARDS: None

SECTION III -- COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS #	WT %
Polyolefin	9003-27-4	10-50 %

SECTION IV -- FIRST AID MEASURES

INHALATION: Move subject to fresh air. If victim is not breathing, perform artificial respiration. Administer oxygen if available. Keep victim warm and at rest. Seek medical attention as soon as possible.
SKIN: Flush with large amount of water or wash with soap and water. Seek medical attention as soon as possible.
EYES: Flush eyes with flowing water at least 15 minutes. Get medical attention. Do not use any



ENVIROKLEEN®

1101 3rd Street Southeast
Canton, OH 44707 USA
330.456.3121
800.321.0699
www.midwestind.com

SAFETY DATA SHEET

INGESTION: eye ointment. Remove contact lenses.
EnviroKleen has a laxative effect and will be eliminated quickly. Seek medical attention. NEVER GIVE FLUIDS OR INDUCE VOMITING IF PATIENT IS UNCONSCIOUS OR HAVING CONVULSIONS.

RECOMMENDATION TO FIREFIGHTERS ON SPECIAL PROTECTIVE EQUIPMENT OR PRECAUTIONS:
Respirator and eye protection are required for firefighting personnel. May need to use SCBA (self contained breathing apparatus as required.)

SECTION V -- FIREFIGHTING MEASURES

EXTINGUISHING MEDIUM: As this material is virtually not-flammable, use proper equipment to fight surrounding fire.

SPECIAL FIREFIGHTING PROCEDURES: If a tank, railcar or tank truck is involved in a fire isolate for 0.5 miles in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from the area and let the fire burn itself out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of the tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SPECIAL HAZARDS: Do not cut, weld, heat, drill, or pressurize empty container.

SECTION VI -- ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Safety glasses and gloves

SPILL AND LEAK PROCEDURES: ELIMINATE ALL IGNITION SOURCES. Stop leak without risk and contain spill. Absorb with inert absorbent materials such as clay or sand. Place absorbent in closed metal containers for later disposal or burn in appropriate facility. Keep spills out of sewers and open bodies of water.

SECTION VII -- HANDLING AND STORAGE

STORAGE: Keep in cool, dry, ventilated storage area and in closed containers. Keep away from sources of ignition and oxidizing materials.

HANDLING: KEEP AWAY FROM SOURCES OF IGNITION. Do not reuse empty containers. Practice good hygiene. Wash hands before eating. Launder clothes before reuse. Discard saturated



ENVIROKLEEN®

1101 3rd Street Southeast
Canton, OH 44707 USA
330.456.3121
800.321.0699
www.midwestind.com

SAFETY DATA SHEET

leather goods.

SECTION VIII -- EXPOSURE CONTROL/PERSONAL PROTECTION

OSHA PEL (8 hour TWA)	5 mg/m ³ for synthetic product mists.
VENTILATION:	Under normal handling conditions special ventilation is not necessary. If operation generates mist or fumes, use ventilation of keep exposure to airborne contaminants below exposure limits.
RESPIRATORY PROTECTION:	None required if good ventilation is maintained. If mist is generated by heating or spraying, use a NIOSH approved organic respirator with a mist filter.
EYE PROTECTION:	Chemical splash, goggles recommended.
PROTECTIVE CLOTHING:	Clothing to minimize skin contact, long sleeves, boots or shoes. For casual contact PVC gloves are suitable, for prolonged contact use neoprene or nitrile gloves.

SECTION IX -- PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Odor:	None
Vapor Density:	N/D
Solubility in Water:	Insoluble
Relative Density:	0.82-0.87
Melting/Freezing Point:	N/D
VOC Content:	N/D
Viscosity:	25-345 cSt @ 22°C
Flashpoint:	>170°C (338°F)
Flammable Limits LEL:	N/D
Flammable Limits UEL:	N/D
Odor Threshold:	N/D
Initial Boiling Point/Range:	>316°C (601°F)
Vapor Pressure:	Negligible at ambient temperature
Evaporation Rate:	N/D
pH:	N/A, not an aqueous solution or emulsion
Octanol/Water Coefficient:	N/D
Decomposition Temperature:	N/D
Flammability (solid/gas):	N/A
Auto Ignition Temperature:	351°C (664°F)

SECTION X -- STABILITY AND REACTIVITY



ENVIROKLEEN®

1101 3rd Street Southeast
Canton, OH 44707 USA
330.456.3121
800.321.0699
www.midwestind.com

SAFETY DATA SHEET

REACTIVITY:	None
CHEMICAL STABILITY:	Stable
CHEMICAL INCOMPATIBILITY:	Can react with strong organic oxidizing materials
HAZARDOUS DECOMPOSITION PRODUCTS:	Thermal decomposition in the presence of air may yield carbon monoxide and/or carbon dioxide, smoke, hydrocarbons and irritating fumes.
HAZARDOUS POLYMERIZATION:	Does not occur under normal industrial conditions.
CONDITIONS TO AVOID:	Excessive heat and flame

SECTION XI -- TOXICOLOGICAL INFORMATION

EFFECTS OF OVEREXPOSURE

INHALATION:	Inhalation is highly unlikely, however, prolonged or repeated inhalation of fumes or mists may cause irritation to the respiratory tract. Product deposits in lungs may lead to fibrosis and reduced pulmonary function.
SKIN:	It is not a skin irritant, however, prolonged or repeated contact may cause skin irritation, dermatitis, or oil acne.
EYES:	Prolonged or repeated contact may be irritating to eyes. Will not cause permanent damage.
INGESTION:	Relatively non-toxic to digestive tract.
CARCINOGENICITY:	Based on studies to date EnviroKleen® is not known to be carcinogenic to humans. ACGIH (mists) - Based on available human studies, exposure to product mist alone has not demonstrated to cause human effects at levels below 5 mg/m3. IARC - IARC group 3; cannot be classified as to carcinogenicity to humans. NTP - No studies were found. IRIS - No studies were found. OSHA - OSHA PEL (8 hour TWA) = 5 mg/m3 for synthetic product mists.
GERM CELL MUTAGENICITY	N/D
REPRODUCTIVE TOXIN:	Based on data to date, it does not pose a reproductive risk.

SECTION XII -- ECOLOGICAL INFORMATION

EnviroKleen Aquatic Toxicity Test Results

*Methods for Measuring the Acute Toxicity of Effluents and Receiving Water to Freshwater and Marine Organisms, EPA/600/4-90/027F.

*Short-term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Water to Freshwater



ENVIROKLEEN®

1101 3rd Street Southeast
Canton, OH 44707 USA
330.456.3121
800.321.0699
www.midwestind.com

SAFETY DATA SHEET

Organisms, EPA/600/4-91/002.

*Short-term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Water to Marine and Estuarine Organisms, EPA/600/4-91/003.

	Ceriodaphnia dubia	Fathead minnow	Americamysis bahia	Rainbow Trout
Acute/Survival (mg/L)				
LC50	>100	>100	>100	>100
NOEC	>100	>100	>100	>100
LOEC	>100	>100	>100	>100
Chronic/Survival (mg/L)				
LC50	>100	>100	>100	>100
NOEC	>100	>100	>100	>100
LOEC	>100	>100	>100	>100
Chronic/Growth/Reproduction (mg/L)				
LC50	>100	>100	>100	>100
NOEC	>100	>100	>100	>100
LOEC	>100	>100	>100	>100

See attached test results:

1. ABC Laboratories, Inc. Americamysis bahia, Fathead minnow, Ceriodaphnia dubia.
2. ABC Laboratories, Inc. Rainbow trout

LC50 - Lethal Concentration, 50%

NOEC - No Observable Effects Concentration

LOEC - Lowest Observable Effects Concentration

The LC₅₀ level is the lethal concentration of the chemical under test that kills 50% of the test organisms in the specified amount of time. According to the EPA-540-9-85-006, suggested toxicity criteria for materials are listed in the table below.

Comparison of the EPA guidelines to the LC₅₀ levels of all species show that EnviroKleen® is practically non-toxic to all species. When used and applied properly, EnviroKleen® is not known to pose any ecological problems.

SECTION XIII -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD Consult your local authorities for regulations. Preferred waste management: recycle or

